

DRIVEGUARD™ SENSOR



CT-6 Sensor Probe



CT-6 Sensor Probe has a custom length of direct burial cable attached at the factory. Attached cable comes in increments of 50', from 100' to 500'; cut in increments of 100', from 500' to 3000'. Direct burial cable makes conduit unnecessary. Cable is polyurethane coated, making splicing in the field possible.

SYSTEM FEATURES

- Use with DriveGuard, Ultra, and Integrator systems and with Pioneer Free
- Exit system (which use the CT-2B, CF-2C and CT-3BG control units respectively)
- Covers 12-foot-wide driveway when buried beside driveway
- Maintenance-free, solid construction, sealed and weatherproof
- Sensor probe and wire do not require conduit
- Tough polyurethane coated for maximum protection
- May be spliced in the field with an underground splice kit (see page 17)
- Fully shielded to avoid false alarms caused by RF noise
- Custom length of continuous cable from 10 ft. to 3,000 ft.
- Attached cable in 50 ft. increments up to 500 ft.; in 100 ft. increments from 500 ft. up to 3,000 ft.

Technical Specifications

	CT-6
Temp. Range	-40° F. - +250° F.
Dimensions	16½" x 1 3/8" dia.
Weight	3.5 lbs. with 100 ft. of cable
Other	500 to 800 ohms coil resistance depending on wire length

OVERHEAD VIEW OF DRIVEWAYS

